



(TECHNICAL) PRODUCT INFORMATION
AT-B

Standard version

- ✓ Ideal low step-in height with step up plate.
- ✓ Front drum brake, rear hand brake.
- ✓ Easy-to-use parking brake.
- ✓ Schwalbe anti-puncture tyres.
- ✓ Available with various (gear) hubs.
- ✓ Closed chaincase and shielded drive.
- ✓ Smooth riding and steering thanks to differential on rear wheels.
- ✓ Low centre of gravity so very stable

Colors

- Satin blue (RAL 5015)
- Satin pink (RAL 3014)
- Custom RAL color at additional charge (excluding fluorescent colors).

RAL
5015

RAL
3014

Most common options & accessories

- Balance pedals
- Footrests
- Hip- and back support
- Rear view mirror
- Push bar

Find more options on the AT-B price list or configure your AT-B via the configurator on the website.



Other features

Standard

Weight in kg	74
Material frame	anti-corrosion treated steel grade
Exterior	epoxy coating (less environmentally harmful)
Seat post	fixed aluminium
Handlebar stem	ergonomic, adjustable
Rear wheel	16"
Front wheel	20"
Tyres	Schwalbe Marathon Plus (anti-puncture)

Pedal support (optional)

Motor	Bafang front wheel motor 65 Nm
Battery	Bafang 43V, 450Wh (optional 750 Wh). Lockable and removable.
Sensor	rotation (Speed)
Display	monochrome
Weight in kg	9

Dimensions

Part	
Length overall in mm (L)	1360
Width in mm	625
Frame size in mm	310
Inner leg length in mm (X)	470-650
Maximum load in kg	60
Crank length in mm	110

