

Standard version

- Oriver at the reqar, passenger at the front.
- < Easily operated hydraulic brakes.
- 🥪 Optional co-steering, co-pedalling.
- 🥪 Schwalbe anti-puncture tyres.
- Bright LED lighting, front and rear.
- 🥪 Available with various (gear) hubs.
- Closed chaincase.
- Low centre of gravity so very stable.
- < Two sizes.

Colors

- Silk white (RAL 9016)
- Silk pearl grey (RAL9023)
- Custom RAL color at additional charge (excluding fluorescent colors).



Most common options & accessories

- Balance pedals
- Multiple saddle types
- Backrest
- Rear view mirror
- Stick holders

Find more options on the Copilot pricelist or configure your Copilot via the configurator on the website.



Other features

Frame material

Seat post front

Seat post rear

Rear wheel

Front wheel

Tyres

Handlebar stem

Standard Weight in kg

Exterior

Copilot 24	í.
29 (witho	ut pedal assistance)
anti-corro	sion treated steel
grade epo	oxy coating (less
environm	entally harmful)
front fixe	d aluminium, several sizes rear
fixed alun	ninium, springy
ergonomi	c, adjustable
24"	
24"	
Schwalbe	Marathon Plus (anti-puncture)

Copilot 26

29 (without pedal assistance) anti-corrosion treated steel grade epoxy coating (less environmentally harmful) front fixed aluminium, several sizes rear fixed aluminium, springy ergonomic, adjustable 26" 26" Schwalbe Marathon Plus (anti-puncture)

Dimensions

Part	Copilot 24	Copilot 26
Total length in mm (L)	2470	2580
Frame size front in mm	320	460
Frame size rear in mm	430	460
Inner leg length front in mm (B)	440*-850**	570*-980**
Inner leg length rear in mm (B)	710-940	770-930
Step-in height front in mm (E)	450	470
Maximum load in kg	180	180
Crank length in mm	170	170

Crank length in mm

* Can be adjusted when using crank shorteners and seat post lowering. ** Can be adjusted when using T seat post, 400 mm.

Pedal support (optional)

Motor Battery	Bafang rear-wheel motor 65 Nm Bafang 43V, 450Wh (optional 750 Wh) Lockable and removable
Sensor	power (Torque)
Display	large, monochrome
Weight	total 9 kg



