

Standard version

- Ideal low step-in height with step up plate.
- Front drum brake, rear hand brake.
- Easy-to-use parking brake.
- Schwalbe anti-puncture tyres.
- Available with various (gear) hubs.
- Closed chaincase and shielded drive.
- Smooth riding and steering thanks to differential on rear wheels.
- Low centre of gravity so very stable

Colors

- Satin blue (RAL 5015)
- Satin pink (RAL 3014)
- Custom RAL color at additional charge (excluding fluorescent colors).



Most common options & accessories

- Balance pedals
- Footrests
- Hip- and back support
- Rear view mirror
- Push bar

Find more options on the AT-B price list or configure your AT-B via the configurator on the website.



Other features

| Standard | | |
|----------------|--|--|
| Weight in kg | 74 | |
| Material frame | anti-corrosion treated steel grade | |
| Exterior | epoxy coating | |
| | (less environmentally harmful) | |
| Seat post | fixed aluminium | |
| Handlebar stem | ergonomic, adjustable | |
| Rear wheel | 16" | |
| Front wheel | 20" | |
| Tyres | Schwalbe Marathon Plus (anti-puncture) | |

Pedal support (optional)

| Motor | |
|--------------|--|
| Battery | |
| | |
| Sensor | |
| Display | |
| Weight in kg | |

Bafang front wheel motor 65 Nm Bafang 43V, 450Wh (optional 750 Wh). Lockable and removable. rotation (Speed) monochrome 9

Dimensions

| Part | |
|-----------------------------|---------|
| Length overall in mm (L) | 1360 |
| Width in mm | 625 |
| Frame size in mm | 310 |
| Inner leg length in mm (X) | 470-650 |
| Entry height in mm | 260 |
| Entry length of frame in mm | 340 |
| Crank length in mm | 110 |
| Maximum load in kg | 60 |



