

(TECHNICAL) PRODUCT INFORMATIO

Standard version

- \checkmark Driver at the rear, passenger at the front.
- 🥣 Easily operated hydraulic brakes.
- 🥑 Extra stable with two wheels at front.
- 🥑 Optional co-pedalling.
- 🥑 Schwalbe anti-puncture tyres.
- ✓ Bright LED lighting, front and rear.
- Available with various (gear) hubs.
- 🥑 Closed chaincase.
- Low centre of gravity so very stable.
- 🧹 Two sizes.
- 🥑 Detachable front section.

Colors

- Silk white (RAL 9016)
- Silk pearl grey (RAL9023)
- Custom RAL color at additional charge (excluding fluorescent colors).

RAL RAL 9016 9023

Most common options & accessories

- Balance pedals
- Multiple saddle types
- Backrests
- Rear view mirror
- Switchable freewheel

Find more options on the Copilot 3 pricelist or configure your Copilot 3 via the configurator on the website.



Other features

Standard	Copilot 3-24	Copilot 3-26
Weight in kg	30	31
Material frame	anti-corrosion treated steel	anti-corrosion treated steel
Exterior	grade epoxy coating	grade epoxy coating
	(less environmentally harmful)	(less environmentally harmful)
Seat post front	front fixed aluminium, several sizes rear	front fixed aluminium, several sizes
Seat post rear	fixed aluminium,	suspension
Handlebar stem rear	ergonomic, adjustable	ergonomic, adjustable
Front wheels	20 x 1,75 (47-406)	20 x 1,75 (47-406)
Rear wheel	24 x 1,75 (47-507)	26 x 1,75 (47-559)
Tyres	Schwalbe Marathon Plus (anti-puncture)	Schwalbe Marathon Plus (anti-puncture)

Dimensions

Part	Copilot 3-24	Copilot 3-26
Length overall in mm (H)	2040-2080	2150
Frame size front in mm	385	510
Frame size rear in mm	460	515
Inner leg length front in mm (A)	500-780	690-970
Inner leg length rear in mm (B)	710-900	850-990
Step-in height front in mm (G)	400	400
Maximum load in kg	180	200
Crank length in mm front	150	150
Crank length in mm rear	170	170
Width in mm	890	890

Pedal support (optional)

Motor	Bafang rear-wheel motor 65 Nm
Battery	Bafang 43V, 750Wh
	lockable and removable
Sensor	power (Torque)
Display	large, monochrome
Weight	total 9 kg



