

Standard version

- Oriver at the reqar, passenger at the front.
- < Easily operated hydraulic brakes.
- 🥪 Optional co-steering, co-pedalling.
- 🥪 Schwalbe anti-puncture tyres.
- Bright LED lighting, front and rear.
- 🥪 Available with various (gear) hubs.
- Closed chaincase.
- Low centre of gravity so very stable.
- < Two sizes.

Colors

- Silk white (RAL 9016)
- Silk pearl grey (RAL9023)
- Custom RAL color at additional charge (excluding fluorescent colors).



Most common options & accessories

- Balance pedals
- Multiple saddle types
- Backrest
- Rear view mirror
- Stick holders

Find more options on the Copilot pricelist or configure your Copilot via the configurator on the website.



Other features

Seat post front Seat post rear Handlebar stem Front wheel Rear wheel Tyres

Copilot 24 29 (without pedal assistance) anti-corrosion treated steel grade epoxy coating (less environmentally harmful) front fixed aluminium, several sizes rear fixed aluminium, springy ergonomic, adjustable 24 x 1,75 (47-507) 24 x 1,75 (47-507) Schwalbe Marathon Plus (anti-puncture)

Copilot 26


29 (without pedal assistance) anti-corrosion treated steel grade epoxy coating (less environmentally harmful) front fixed aluminium, several sizes rear fixed aluminium, springy ergonomic, adjustable 26 x 1,75 (47-559) 26 x 1,75 (47-559) Schwalbe Marathon Plus (anti-puncture)

Dimensions

Part	Copilot 24	Copilot 26
Total length in mm (L)	2470	2580
Frame size front in mm	320	460
Frame size rear in mm	430	460
Inner leg length front in mm (B)	440*-850**	570*-980**
Inner leg length rear in mm (B)	710-940	770-930
Step-in height front in mm (E)	450	470
Saddle height to ground, front in mm	640-770	810-1020
Saddle height to ground, rear in mm	810-990	900-1060
Maximum load in kg	180	180
Crank length in mm	170	170

Pedal support (optional)

Motor Battery	Bafang rear-wheel motor 65 Nm Bafang 43V, 450Wh (optional 750 Wh) Lockable and removable
Sensor	power (Torque)
Display	large, monochrome
Weight	total 9 kg





* Can be adjusted when using crank shorteners and seat post lowering. ** Can be adjusted when using T seat post, 400 mm.